

2380A

FLAT-FRONT BI-RADIAL™ HORN



FEATURES:

Uniform horizontal on and off axis frequency response

Precise horizontal and vertical pattern control

Full horn loading to 500 Hz

Flat front and compact size

Lightweight construction

49 mm (2 in) throat entry

The JBL 2380A Bi-Radial™ horn¹ is designed for flush cabinet mounting or compact cluster applications. The 2380A has a nominal coverage pattern of 90° horizontal x 40° vertical. The horn provides uniform on and off axis frequency response from 500 Hz to beyond 16 kHz in the horizontal plane and 2 kHz to 16 kHz in the vertical plane with constant directivity above 2 kHz. The horns' small vertical mouth dimension (just slightly larger than the compression driver used to drive the horn) allows very compact single and multiple horn/driver systems to be put together. Should vertical pattern control be required below 2 kHz, two or more horns may be stacked vertically to restore full Bi-Radial™ performance.

The exceptionally consistent horizontal dispersion eliminates the midrange narrowing and high frequency beaming problems typically associated with conventional horn designs. Additionally, the highly predictable performance of the 2380A greatly simplifies cluster design. The need for horn overlapping is minimized and lobing and comb filter effects are virtually eliminated.

Computer-aided design techniques were used to derive the horn contours in the horizontal and vertical planes. Utilizing sidewall contours based on a polynomial power series formula, the horn design yields smooth response, low distortion, and

even coverage. This design avoids the performance disadvantages of horns that feature sharp flare transitions and flat sidewalls. The Bi-Radial™ compound flare configuration provides constant coverage over defined, solid angles. To ensure light weight, superior strength, and freedom from resonances, the horn bell is constructed of molded structural foam.

The 2380A will accept the 49 mm (2 in) diameter throat 2441, 2445, or 2485 compression driver. With the addition of the 2327 adapter, the horn will also accept the 25 mm (1 in) throat 2425 driver.


U.S. Patent No. 4,308,932. Foreign patents pending.

SPECIFICATIONS:


Throw: Short	
Horizontal Coverage:	
Angle Degrees (-6 dB):	100 (+23, -23)
Average Range:	500 Hz - 16 kHz
Vertical Coverage:	
Angle Degrees (-6 dB):	40 (+11, -11)
Average Range:	2 kHz - 16 kHz
Directivity Factor (Q):	10.7 (+1.3, -2.51)
Directivity Index (Di):	10.3 dB (+1.0, -1.4)
Average Range:	1 kHz - 16 kHz
Usable Low-Frequency Limit:	400 Hz
Minimum Recommended Crossover Frequency:	500 Hz
Axial Pressure Sensitivity:	112 dB SPL, 1 W @ 1 m

Construction	Molded structural foam (nominal 10 mm (0.38 in) wall thickness)
Overall Dimensions:	
Mouth Height:	279 mm [11 in]
Mouth Width:	445 mm [17.5 in]
Length:	236 mm [9.28 in]
Mounting Dimensions:	
Rear Height:	235 mm [9.25 in]
Rear Width:	400 mm [15.75 in]
Baffle Cutout Required: (Front mounting only)	
Height:	238 mm [9.37 in]
Width:	403 mm [15.78 in]
Net Weight:	2.2 kg [6 lb]
Shipping Weight:	4.6 kg [10 lb]


Measured on axis in the far field with 1 watt input (4.0 volts RMS, 16 ohms) and referenced to 1 meter distance using the inverse square law. Listed sound pressures (SPL re 20 µPa) represent an average from 1 kHz to 4 kHz using the 2441 or 2445 driver.




Beamwidth vs Frequency




Directivity vs Frequency




Frontal Isobar Contours




500 Hz octave bandwidth constant sound pressure contours of 0 to -15 dB in steps of -3 dB. The contours are plotted on polar grid lines with 0° on axis being the center of the plot. The data was gathered by taking an octave polar plot at all oblique angles from 0° (horizontal) to 90° (vertical) in steps of 15°. Same test conditions as horizontal polar response.




1 kHz octave bandwidth constant sound pressure contours. Same conditions as 500 Hz contours.





2 kHz octave bandwidth constant sound pressure contours. Same conditions as 500 Hz contours.



4 kHz octave bandwidth constant sound pressure contours. Same conditions as 500 Hz contours.





8 kHz octave bandwidth constant sound pressure contours. Same conditions as 500 Hz contours.





Harmonic distortion. Second and third harmonic distortion curves of the 2380A with 1 watt (4.0 V RMS) and 10 watts (12.65 V RMS) applied to the JBL Model 2445 compression driver. Measured on axis at a distance of 1 meter in a reflection-free environment.

Frequency response and impedance. Frequency response of the 2380A, measured on axis at a distance of 1 meter with 1 watt (4.0 V RMS) applied to a JBL Model 2445 compression driver, in a reflection-free environment, with impedance vs. frequency curve.



Horizontal off-axis response. Horizontal off-axis response taken at 15 degree intervals out to 60° off axis. Both normalized (equalized flat on axis) and unnormalized responses are shown.



Vertical off-axis response. Vertical off-axis response taken at 15° intervals out to 60° off axis. Both normalized (equalized flat on axis) and unnormalized responses are shown.

JBL continually engages in research related to product improvement. New materials, production methods, and design refinements are introduced into existing products without notice as a routine expression of that philosophy. For this reason, any current JBL product may differ in some respect from its published description, but will always equal or exceed the original design specifications unless otherwise stated.

